

TerraMai's Acacia Metro Flooring & Paneling is a lustrous mosaic of rich brown and golden tones with light and dark contrasting grain. A good fit for many environments, Acacia Metro with its color variation and pattern creates excitement and life in any space.

#### Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
Yes	Yes	Yes	No	No

#### Approved Installation Methods

- Nail/Staple/Cleat
- Glue (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

#### Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

#### Options

Class A Flame Retardant

#### Profile

T&G, Square Edge, End Matched



# TERRAMAI

ACACIA METRO  
ENGINEERED  
FLOORING & PANELING

Wood is a natural material. Variation in color and grain pattern are to be expected.  
For more information or to place an order, please contact your [local TerraMai Rep.](#)




<b>SKU</b>	697
<b>Finish Option</b>	Poly
<b>Face Width</b>	7-5/8" (194mm)



<b>SKU</b>	698
<b>Finish Option</b>	Clear Oil
<b>Face Width</b>	7-5/8" (194mm)



<b>SKU</b>	745
<b>Finish Option</b>	Driftwood
<b>Face Width</b>	7-5/8" (194mm)



<b>SKU</b>	747
<b>Finish Option</b>	Wire White - Wire Brush
<b>Face Width</b>	7-5/8" (194mm)



<b>SKU</b>	748
<b>Finish Option</b>	Wire Dark - Wire Brush
<b>Face Width</b>	7-5/8" (194mm)

Species	Acacia
Source	Wear layer of post-manufacturing reclaimed Acacia from Southeast Asia.
Character	Prefilled holes.
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	9/16" (14mm)
Width	7-5/8" (194mm)
Length	47-3/16" (1,199mm)
Construction	Engineered
Wear Layer	5/32" (4mm)
# of Backer Plies	7
Filler	Sawdust & Epoxy
Janka/Hardness	900 lbs (4 kN)
Moisture Content	6%-9%
Knots	Occasional small, sound knots
Nail Holes	Very occasional prefilled holes
Saw Marks	No
Grain	Mixed Grain
Density	
Packaging	Boxed

\*Custom finishes available.

For more information on installation guidelines, please visit [TerraMai.com](https://TerraMai.com) and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

## CERTIFICATIONS



VOC Reduction - Feature 4  
Toxic Material Reduction - Feature 25

## CONTRIBUTES TO TO LEED® V4

EQ Credit: Low-Emitting Materials - Flooring  
(1-3 Points)