



Award winning, beautifully weathered redwood paneling. Classic naturally distressed redwood patina associated with the Northern California coast. Material is also excellent for cladding, wainscoting and similar applications.

### Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
No	Yes	Yes	Yes	No

### Approved Installation Methods

- Nail/Staple/Cleat
- Glue & Nail (Interior - 100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

### Acclimation

For interior applications, the planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information. For exterior siding applications, acclimate per the [TerraMai Siding & Decking Acclimation Guide](#).

### Options

Class A Flame Retardant

### Profile

S4S - T&G, Square Edge



# TERRAMAI

## LOST COAST REDWOOD SURFACED *SOLID* PANELING

Wood is a natural material. Variation in color and grain pattern are to be expected.  
For more information or to place an order, please contact your [local TerraMai Rep.](#)



<b>SKU</b>	723
<b>Finish Option</b>	Clear Oil*
<b>Face Width</b>	5" (127mm)

<b>SKU</b>	624
<b>Finish Option</b>	Clear Oil*
<b>Face Width</b>	7" (178mm)

\* For exterior applications, unfinished or exterior grade finishes must be used.

Species	<i>Sequoia sempervirens</i>
Source	Reclaimed Redwood from aging structures in the San Francisco Bay Area.
Character	Heavy to light weathering. Occasional unfilled fastener, insect or other through holes. Tight knots up to 3" wide with some missing knots. Seasoning checks and end-splits not to exceed 4". Possible oxide and other staining, along with other evidence of prior use and history.
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	1/2" (13mm)
Widths	5" (127mm) 7" (178mm)
Lengths	2-5' (610-1,524mm)
Construction	Solid
Wear Layer	3/16" (5mm)
# of Backer Plies	N/A
Filler	No
Janka/Hardness	450 lbs (2 kN)
Moisture Content	6%-9%
Knots	Tight knots up to 1-1/2" with some missing knots, seasoning checks, and end splits not to exceed 4". Possible oxide and other staining.
Nail Holes	Occasional unfilled fastener, insect or other through holes.
Saw Marks	Yes
Grain	Mixed Grain
Density	26 lbs/ft <sup>3</sup> (704.8 kg/m <sup>3</sup> )
Packaging	Palletized

\*Custom finishes available.

For more information on installation guidelines, please visit [TerraMai.com](https://TerraMai.com) and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

## CERTIFICATIONS



FSC Recycled 100% - FSC-C021798



HPD Certified

## CONTRIBUTES TO LEED® V4

EQ Credit: Low-Emitting Materials – Flooring  
(1-3 Points)

MR Credit: Building Life-Cycle Impact Reduction, Option 3  
(2-5 Points)