



Gorgeous reclaimed redwood siding recycled from various structures in the San Francisco Bay Area. Surfaced redwood removes the weathered patina allowing the classic burgundy redwood with amber tones to shine through.

**Table 1 - Approved Applications**

	INTERIOR			EXTERIOR		
	Floors	Walls	Ceilings	Decking	Siding	Soffits
<b>Application Area</b>	No	Yes	Yes	No	Yes	Yes
<b>Installation Method</b>	N/A	1. Nails into structural members 2. Nail & Glue	1. Nails into structural members 2. Nail & Glue	N/A	1. Nails*	1. Nails*

\* See Siding Installation Guidelines for requirements.





### Acclimation

Wood siding must be allowed time to reach its equilibrium moisture content with the location where it will be installed. Upon receiving your material, remove the siding from the packaging and visually inspect boards for defects, including boards from the top, bottom and middle. Cross-stack the material with stickers (spacers between each layer) to allow air circulation on all sides of all boards. Stickers must be a maximum of 12" apart to prevent the siding from warping. Make sure to place in an area where there will be good air flow through the stack. The stack must be protected at all times from direct sunlight and liquid water, including irrigation systems, all forms of precipitation, and dew formation. Follow all requirements in the Siding & Decking Acclimation Guidelines that can be found at [Terramai.com/acclimation](https://Terramai.com/acclimation).

### Custom

- Trim
- Board thickness
- Board widths
- Reveal widths
- Finishes

Table 2 - Profiles

Profile	Beveled Lap	Board & Batten	Rainscreen	Shiplap
				
<b>Installation Orientation Options</b>	Horizontal or Vertical	Vertical Only	Horizontal or Vertical	Horizontal or Vertical
<b>Milling</b>	Surfaced four sides (S4S) with Beveled Lap profile, 1/4" reveal. Unfilled.	Surfaced four sides (S4S) square edge profile on boards and battens. Unfilled.	Surfaced four sides (S4S) with rainscreen profile, 1/4" reveal. Unfilled.	Surfaced four sides (S4S) with shiplap profile, 1/4" reveal. Unfilled.
<b>Width</b>	6-3/4"	8-1/2" Center to Center (7-1/2" Boards spaced 1" apart, gap covered by 3-1/2" Battens)	6-3/4"	7"
<b>Reveal (Included in Width)</b>	1/4"	1" (Covered by Battens)	3/16"	1/4"
<b>Thickness</b>	5/8"	1-1/4" Total (5/8" Boards + 5/8" Battens)	11/16"	5/8"



Wood is a natural material. Variation in color and grain pattern are to be expected. For more information or to place an order, please contact your [local TerraMai Rep.](#)

Table 3 - SKU & Finish Data

	FINISH	SKU
<b>Beveled Lap</b> 	Unfinished	1542
	Clear Protective Sealer	1543
	Color Protecting Exterior Finish	1544
<b>Board &amp; Batten</b> 	Unfinished	1545
	Clear Protective Sealer	1546
	Color Protecting Exterior Finish	1547
<b>Rainscreen</b> 	Unfinished	1548
	Clear Protective Sealer	1549
	Color Protecting Exterior Finish	1550
<b>Shiplap</b> 	Unfinished	588
	Clear Protective Sealer	1211
	Color Protecting Exterior Finish	1541

Species	<i>Sequoia sempervirens</i>
Source	Reclaimed Redwood from aging structures in the San Francisco Bay Area.
Character	Heavy to light weathering. Occasional unfilled fastener, insect or other through holes. Tight knots up to 3" wide with some missing knots. Seasoning checks and end-splits not to exceed 4". Possible oxide and other staining, along with other evidence of prior use and history.
Finish*	Clear Protective Sealer or Color Protecting Exterior Finish.
Thickness	Varies by Profile. See Table 2 - Profiles
Width	Varies by Profile. See Table 2 - Profiles
Lengths	2' - 5'-6" (610mm - 1676mm) random lengths.
Construction	Solid
# of Backer Plies	N/A
Filler	N/A
Janka/Hardness	450 lbs (2 kN)
Moisture Content	12% - 16%
Knots	Tight knots up to 1-1/2" with some missing knots, seasoning checks, and end splits not to exceed 4". Possible oxide and other staining.
Nail Holes	Yes
Saw Marks	No
Grain	Mixed Grain
Density	26 lbs/ft <sup>3</sup> (704.8 kg/m <sup>3</sup> )
Packaging	Palletized

\*Custom finishes available.

For more information on installation guidelines, please visit [TerraMai.com](http://TerraMai.com) and see [Siding Installation Guidelines](#).

## CERTIFICATIONS



FSC Recycled 100% - FSC-C021798



[HPD v2.1.1](#)

## CONTRIBUTES TO LEED® V4

EQ Credit: Low-Emitting Materials  
(1-3 Points)

MR Credit: Building Life-Cycle Impact Reduction, Option 3  
(2-5 Points)