



Subdued elegance for any type of space. Reclaimed American Black Walnut with a low-VOC poly or natural oil finish. Also available unfinished or in custom tints and textures.

### Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
Yes*	Yes	Yes	No	No

### Approved Installation Methods

- Nail/Staple/Cleat
- Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

### Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

### Options

Class A Flame Retardant

### Profile

T&G, Square Edge, End Matched



\* Note on Flooring Applications: Walnut is on the softer end of the scale compared to most other hardwoods. As such, it will more easily develop a patina of use evidenced in heel marks and other indentations. To many, this is the warmth and organic nature they expect to see in a wood floor. In a lower impact residential use, such wear is typically less noticeable than in a high traffic commercial space. In a high traffic commercial space, you may decide that one of our harder woods is more suitable. Assuming you do select this walnut, you may choose to have TerraMai finish the material in an oil rather than a polyurethane (wear is then somewhat less noticeable).

# TERRAMAI

Wood is a natural material. Variation in color and grain pattern are to be expected.  
For more information or to place an order, please contact your [local TerraMai Rep.](#)



<b>SKU</b>	458
<b>Finish Option</b>	Clear Oil
<b>Face Width</b>	5" (127mm)



<b>SKU</b>	487
<b>Finish Option</b>	Oyster Wash*
<b>Face Width</b>	5" (127mm)



<b>SKU</b>	708
<b>Finish Option</b>	Poly
<b>Face Width</b>	5" (127mm)

<b>SKU</b>	792
<b>Finish Option</b>	Poly
<b>Face Width</b>	3" (76mm)

\* Oyster Wash finish is not recommended for flooring applications.

Species	<i>Juglans nigra</i>
Source	Pre-consumer recycled black walnut wear layer salvaged from manufacturing facilities in the Midwestern U.S.
Character	Typical walnut tones ranging from lighter to darker material. These color tones may blend over time as exposure to light softens the color range.
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	9/16" (14mm)
Widths	5" (127mm) 3" (76mm)
Lengths	1' - 7' (305 - 2,134mm)
Construction	Engineered
Millwork	Reclaimed walnut wear layer at 1/8" thick over an FSC-certified substrate. Three-ply, single strip construction. Tongue & groove profile with micro-bevel. End-matched.
Wear Layer	1/8" (3mm)
# of Backer Plies	3
Filler	N/A
Janka/Hardness	1,010 lbs (4.5 kN)
Moisture Content	6%-9%
Knots	Very occasional small and sound tight knots
Nail Holes	No
Saw Marks	No
Grain	Quarter-Sawn Vertical Grain
Density	38 lbs/ft <sup>3</sup> (609 kg/m <sup>3</sup> )
Recycled Content	22% Pre-Consumer
Packaging	Boxed <ul style="list-style-type: none"> <li>• 17.5 square feet per box for 5" wide</li> <li>• 21 square feet per box for 3" wide</li> </ul>

\*Custom finishes available.

For more information on installation guidelines, please visit [TerraMai.com](http://TerraMai.com) and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

## CERTIFICATIONS



FSC Mix 78% - FSC-C021798



FloorScore® -SCS-FS-03865



VOC Reduction - Feature 4  
Toxic Material Reduction - Feature 25

## CONTRIBUTES TO LEED® V4

EQ Credit: Low-Emitting Materials - Flooring  
(1-3 Points)