



A classic example of what TerraMai does best - great looking, soulful reclaimed wood products designed and built for high-volume commercial projects. Perfect for residential and smaller commercial projects as well. We call this flooring & paneling 'Mission Oak' not only to evoke the reverential use of oak during America's Mission and Craftsman eras, but also to reference TerraMai's mission to turn neglected wood into unique, high-performance products developed for the most sophisticated design projects.

Table 1: Approved Applications

	INTERIOR			EXTERIOR		
	Floors	Walls	Ceilings	Siding	Decking	Soffits
Application Area	Yes	Yes	Yes	No	No	No
Installation Method	<ol style="list-style-type: none"> 1. Nails/Staples/Cleats 2. Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 3. Glue (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 	<ol style="list-style-type: none"> 1. Nails/Staples/Cleats to ½" minimum plywood 2. Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 	<ol style="list-style-type: none"> 1. Nails/Staples/Cleats to ½" minimum plywood 2. Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 	N/A	N/A	N/A

Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 30% to 50% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

Options

- Class A Flame Retardant
- Trim:
 - Stair Nosing
 - Edge Trim
 - Quarter Round
 - Corner Trim
 - Baseboard
 - Transition Strips
 - Door & Window Trim

Profile

T&G, Micro Bevel Edge, End Matched



Wood is a natural material. Variation in color and grain pattern are to be expected.
For more information or to place an order, please contact your [local TerraMai Rep.](#)



SKU	1924
Finish Option	Blacksmith
Face Width	4-1/2"



SKU	1925
Finish Option	Pebble
Face Width	4-1/2"



SKU	1926
Finish Option	Tundra
Face Width	4-1/2"



SKU	1927
Finish Option	Slate*
Face Width	4-1/2"

* Slate is not suitable for Flooring applications.

TERRAMAI

MISSION OAK RED
SOLID
FLOORING & PANELING



SKU	1221
Finish Option	Clear Oil
Face Width	3"



SKU	1222
Finish Option	Poly
Face Width	3"

SKU	1223
Finish Option	Clear Oil
Face Width	4-1/2"

SKU	1224
Finish Option	Poly
Face Width	4-1/2"

Species	<i>Quercus rubra</i>
Source	Wear layer made of FSC-certified recycled red oak from industrial shipping in the eastern U.S.
Reclaimed % and Type	100% POST-Consumer
Character	May include occasional prefilled nail and other holes, prefilled surface checking, sound tight knots and other signs of prior history and use.
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	1/2" (13mm)
Width	4-1/2" (114mm)
Lengths	1' - 7' (305mm - 2133mm)
Construction	Solid
Wear Layer	1/8" (3mm)
# of Backer Plies	None
Filler	Black Epoxy
Janka/Hardness	1,220 lbs (5.4 kN)
Moisture Content	6%-9%
Knots	Prefilled surface checks and sound tight knots of all sizes and other signs of prior history and use.
Nail Holes	Occasional prefilled nail and other holes
Saw Marks	No
Grain	Mixed Grain
Density	44 lbs/ft ³ (704.8 kg/m ³)
Packaging	Palletized

*Custom finishes available.

For more information on installation guidelines, please visit TerraMai.com and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

CERTIFICATIONS



FSC Recycled 100% - FSC-C021798



FloorScore® -SCS-FS-03865



VOC Reduction - Feature 4
 Toxic Material Reduction - Feature 25

CONTRIBUTES TO LEED® V4

Responsible Sourcing of Raw Materials
 (1-2 points)

Low-Emitting Materials
 (Possible 3 Points)