



Teak - the 'King of Woods'. Renowned the world over for its beauty and durability. TerraMai's reclaimed teak flooring, paneling and siding products have the rich color, tight grain, and legendary durability only found in old-growth Asian teak. New, plantation-grown teak cannot compare in either looks or durability. The reclamation of this teak helps preserve standing teak forests and gives these amazing woods another lifetime of use and appreciation.

#### Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
Yes	Yes	Yes	No	No

#### Approved Installation Methods

- Nail/Staple/Cleat
- Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

#### Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

#### Options

Class A Flame Retardant

#### Profile

T&G, Square Edge, Back Relieved, End Matched



# TERRAMAI

TEAK FJ  
*SOLID*  
FLOORING & PANELING

Wood is a natural material. Variation in color and grain pattern are to be expected.  
For more information or to place an order, please contact your [local TerraMai Rep.](#)



SKU	625
Finish Option	Poly
Face Width	5-1/2" (140mm)

SKU	626
Finish Option	Clear Oil
Face Width	5-1/2" (140mm)

Species	<i>Tectona grandis</i>
Source	Salvaged from vintage structures in Southeast Asia
Character	Holes pre-filled with teak and/or teak sanding dust mixed with glue.
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	5/8" (16mm)
Width	5-1/2" (140mm)
Length	6' (1,829mm)
Construction	Solid
Wear Layer	1/4" (6mm)
# of Backer Plies	N/A
Filler	Sawdust & Epoxy
Janka/Hardness	1,070 lbs (4.8 kN)
Moisture Content	6%-9%
Knots	Occasional small, sound knots
Nail Holes	Holes pre-filled with teak and/or teak sanding dust mixed with glue
Saw Marks	No
Grain	Mixed Grain
Density	41 lbs/ft <sup>3</sup> (657 kg/m <sup>3</sup> )
Packaging	Boxed <ul style="list-style-type: none"> <li>• 22 square feet per box</li> </ul>

\*Custom finishes available.

For more information on installation guidelines, please visit [TerraMai.com](https://TerraMai.com) and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

## CERTIFICATIONS



FSC Recycled 100% - FSC-C021798

## CONTRIBUTES TO TO LEED® V4

EQ Credit: Low-Emitting Materials – Flooring  
(1-3 Points)

MR Credit: Building Life-Cycle Impact Reduction, Option 3  
(2-5 Points)