



TerraMai's Wide Plank Hickory Flooring & Paneling is a hard-wearing, durable 100% FSC hardwood that originates from the southeastern United States. Hickory can have a fairly consistent grain and color distribution or have a bold look with several different colors and extreme grain patterns presented in one board. Arctic Fox finish softens the variation and, sly like a fox, this material will catch the eye without detracting from the other elements in the space.

Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
Yes	Yes	Yes	No	No

Approved Installation Methods

- Nail/Staple/Cleat
- Glue (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

Options

Class A Flame Retardant

Profile

T&G, Micro Bevel Edge, End Matched



TERRAMAI

WIDE PLANK HICKORY ENGINEERED FLOORING & PANELING

Wood is a natural material. Variation in color and grain pattern are to be expected.
For more information or to place an order, please contact your [local TerraMai Rep.](#)



SKU	875
Finish Option	Poly
Face Width	7" (178mm)

SKU	876
Finish Option	Clear Oil
Face Width	7" (178mm)



SKU	922
Finish Option	Mink
Face Width	7" (178mm)



SKU	923
Finish Option	Arctic Fox
Face Width	7" (178mm)



SKU	924
Finish Option	Fawn
Face Width	7" (178mm)

Species	<i>Carya ovata</i>
Source	FSC certified new wood harvested in the southeastern U.S.
Character	Includes prefilled surface seasoning checks and sound tight knots.
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	1/2" (13mm)
Width	7" (178mm)
Lengths	1' - 7' (305mm - 2133mm)
Construction	Engineered
Wear Layer	1/8" (3mm)
# of Backer Plies	3
Filler	Black Epoxy
Janka/Hardness	1,880 lbs (8.4 kN)
Moisture Content	6%-9%
Knots	Prefilled surface checks and sound tight knots
Nail Holes	No
Saw Marks	No
Grain	Mixed Grain
Density	50 lbs/ft ³ (800.9 kg/m ³)
Packaging	Boxed <ul style="list-style-type: none"> • 24.5 square feet per box

*Custom finishes available.

For more information on installation guidelines, please visit TerraMai.com and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

CERTIFICATIONS



FSC 100% - FSC-C021798



FloorScore® -SCS-FS-03865



VOC Reduction - Feature 4
Toxic Material Reduction - Feature 25

CONTRIBUTES TO LEED® V4

EQ Credit: Low-Emitting Materials - Flooring
(1-3 Points)