



TerraMai's Wide Plank White Oak Flooring & Paneling is a hard-wearing, durable 100% FSC hardwood that originates from the southeastern United States.

Table 1: Approved Applications

	INTERIOR			EXTERIOR		
	Floors	Walls	Ceilings	Siding	Decking	Soffits
Application Area	Yes	Yes	Yes	No	No	No
Installation Method	<ol style="list-style-type: none"> 1. Nails/Staples/Cleats 2. Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 3. Glue (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 	<ol style="list-style-type: none"> 1. Nails/Staples/Cleats to ½" minimum plywood 2. Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 	<ol style="list-style-type: none"> 1. Nails/Staples/Cleats to ½" minimum plywood 2. Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer) 	N/A	N/A	N/A

Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 30% to 50% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

Options


- Class A Flame Retardant
- Trim:
 - Stair Nosing
 - Edge Trim
 - Quarter Round
 - Corner Trim
 - Baseboard
 - Transition Strips
 - Door & Window Trim

Profile

T&G, Micro Bevel Edge, End Matched



Wood is a natural material. Variation in color and grain pattern are to be expected.
For more information or to place an order, please contact your [local TerraMai Rep.](#)



SKU	1005
Finish Option	Poly
Face Width	7" (178mm)


SKU	1193
Finish Option	Clear Oil
Face Width	7" (178mm)



SKU	1192
Finish Option	Bourbon
Face Width	7" (178mm)



SKU	1004
Finish Option	Pale Ale
Face Width	7" (178mm)



SKU	1194
Finish Option	Porter
Face Width	7" (178mm)

Species	<i>Quercus alba</i>
Source	FSC certified new wood harvested in the southeastern U.S.
Reclaimed % and Type	None
Character	Clear grade mixed grain with occasional pin knot
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	1/2" (13mm)
Width	7" (178mm)
Lengths	1' - 7' (305mm - 2133mm)
Construction	Engineered
Wear Layer	1/8" (3mm)
# of Backer Plies	3
Filler	No
Janka/Hardness	1,350 lbs (6 kN)
Moisture Content	6%-9%
Knots	Very occasional small and sound tight knots
Nail Holes	No
Saw Marks	No
Grain	Mixed Grain
Density	47 lbs/ft ³ (752.9 kg/m ³)
Packaging	Boxed, 24.5 square feet per box

*Custom finishes available.

For more information on installation guidelines, please visit [TerraMai.com](https://www.terramai.com) and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

CERTIFICATIONS



FSC 100% - FSC-C021798



FloorScore® -SCS-FS-03865

CONTRIBUTES TO LEED® V4

Responsible Sourcing of Raw Materials
(1-2 points)

Low-Emitting Materials
(Possible 3 Points)