



TerraMai's Wide Plank White Oak Flooring & Paneling is a hard-wearing, durable 100% FSC hardwood that originates from the southeastern United States.

Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
Yes	Yes	Yes	No	No

Approved Installation Methods

- Nail/Staple/Cleat
- Glue (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

Options

Class A Flame Retardant

Profile

T&G, Micro Bevel Edge, End Matched



TERRAMAI

WIDE PLANK WHITE OAK *ENGINEERED* FLOORING & PANELING

Wood is a natural material. Variation in color and grain pattern are to be expected.
For more information or to place an order, please contact your [local TerraMai Rep.](#)



SKU	871
Finish Option	Poly
Face Width	7" (178mm)


SKU	872
Finish Option	Clear Oil
Face Width	7" (178mm)



SKU	925
Finish Option	Bourbon
Face Width	7" (178mm)



SKU	879
Finish Option	Pale Ale
Face Width	7" (178mm)



SKU	930
Finish Option	Porter
Face Width	7" (178mm)

Species	<i>Quercus alba</i>
Source	FSC certified new wood harvested in the southeastern U.S.
Character	Rustic white oak
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	1/2" (13mm)
Width	7" (178mm)
Lengths	1' - 7' (305mm - 2133mm)
Construction	Engineered
Wear Layer	1/8" (3mm)
# of Backer Plies	3
Filler	No
Janka/Hardness	1,350 lbs (6 kN)
Moisture Content	6%-9%
Knots	Very occasional small and sound tight knots
Nail Holes	No
Saw Marks	No
Grain	Mixed Grain
Density	47 lbs/ft ³ (752.9 kg/m ³)
Packaging	Boxed

*Custom finishes available.

For more information on installation guidelines, please visit TerraMai.com and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

CERTIFICATIONS



FSC 100% - FSC-C021798



FloorScore® -SCS-FS-03865

CONTRIBUTES TO LEED® V4

EQ Credit: Low-Emitting Materials - Flooring
(1-3 Points)